

WO9511765

Publication Title:

CONTINUOUS WASHING AND TRANSFER OF ARTICLES TO A CLEAN ROOM

Abstract:

A method and installation for effecting continuous washing and transfer of articles e.g. bottles to a clean room, comprising the steps of: conveying the articles continuously on a conveyor means extending within enclosure means and into a clean room, and within the enclosure means sequentially subjecting the articles to a bactericidal wash and to bactericidal radiation.

Data supplied from the esp@cenet database - <http://ep.espacenet.com>

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁶:

B08B 9/20, B65B 55/10

A1

(11) International Publication Number:

WO 95/11765

(43) International Publication Date:

4 May 1995 (04.05.95)

(21) International Application Number: PCT/GB94/02316

(22) International Filing Date: 21 October 1994 (21.10.94)

(30) Priority Data:

9321993.9

26 October 1993 (26.10.93)

GB

(71) Applicant (for all designated States except US): GLENEAGLES SPRING WATERS COMPANY LIMITED [GB/GB]; The Maltings, Moray Street, Blackford, Perthshire PH4 1QF (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): NEILLE, Graeme, Kennedy [GB/GB]; 26 Poplar Crescent, Perthshire PH1 1HR (GB).

(74) Agent: FRANK B. DEHN & CO.; European Patent Attorneys, Imperial House, 15-19 Kingsway, London WC2B 6UZ (GB).

(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SI, SK, TJ, TT, UA, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ).

Published


With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: CONTINUOUS WASHING AND TRANSFER OF ARTICLES TO A CLEAN ROOM

(57) Abstract

A method and installation for effecting continuous washing and transfer of articles e.g. bottles to a clean room, comprising the steps of: conveying the articles continuously on a conveyor means extending within enclosure means and into a clean room, and within the enclosure means sequentially subjecting the articles to a bactericidal wash and to bactericidal radiation.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgystan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

- 1 -

CONTINUOUS WASHING AND TRANSFER OF
ARTICLES TO A CLEAN ROOM

This invention relates to a method for effecting
5 continuous washing and transfer of articles to a clean
room, and to an installation for use in carrying out
such method.

The invention is concerned particularly, but not
exclusively, with articles in the form of bottles
10 intended to be charged with liquid for human
consumption, for example, mineral water.

In this description, the term "clean room" means a
room-like enclosure associated with a supply of clean
air introduced to maintain a pressure in the clean room
15 slightly greater than ambient atmospheric pressure for
the purpose of inhibiting the entry into the clean room
of air-borne contaminants of any kind. Clean rooms are
known per se and their construction is not a feature of
the present invention.

20 Although the use of clean rooms in the bottling
industry is fairly recent, clean rooms are commonly used
in the pharmaceutical industry. The number of
operations which can be carried out inside the clean
room is, however, very limited. In fact, the only
25 operation generally carried out in the clean room is the
actual filling. Other processes, such as washing the
containers, applying labels, etc are carried out outside
the clean room.

Normally in the pharmaceutical industry, the
30 containers to be filled are treated and sterilized in
batches on the way to the clean room. In a commonly
used system, the containers are loaded from outside into
a box-type chamber where they are washed and sterilized,
usually by heat. The sterilized containers are then

- 2 -

conveyed out of the chamber and then into a clean room for filling.

Although this method is sufficient for pharmaceutical products, where the number of containers is relatively small, the batch-wise transfer process is too slow and inefficient for use in the food and drink bottling industry where the number of bottles to be processed is very large.

Recently, clean rooms have come to be used in the bottling industry. To speed up the process, some systems are arranged to carry out more operations actually within the clean room, such as washing and/or rinsing. This, however, has the disadvantage of introducing contaminants into the clean room.

Other systems use a step-wise process to convey bottles into a washing or rinsing machine and then the rinsed bottles are conveyed out of the rinsing machine and into the clean room. Again, this has the problem of introducing contaminated bottles into the clean room.

According to the present invention, there is provided a method for effecting continuous washing and transfer of articles to a clean room, comprising the steps of:

conveying the articles continuously on a conveyor means extending within enclosure means and into a clean room, and

within the enclosure means sequentially subjecting the articles to a bactericidal wash and to bactericidal radiation.

Preferably, the said method includes the step of inducing an exhaust current from the enclosure means to ensure a continuous air flow therethrough from the clean room.

Preferably, the articles are bottles intended to be charged with mineral water and the bactericidal wash

- 3 -

is water and ozone and the bactericidal radiation is ultraviolet radiation.

Further, according to the present invention, there is provided an installation for use in the continuous washing and transfer of articles to a clean room,
5 comprising:

a continuous conveyor for conveying the articles and extending within enclosure means and into a clean room, an exit from the enclosure means being within the
10 clean room,

a washing means for use in washing the articles and disposed within the enclosure means adjacent an entrance thereto, and

an irradiating means operable to emit bactericidal radiation towards the conveyor and articles thereon and
15 disposed within the enclosure means downstream of the washing means.

Preferably, there is provided a venting means adjacent the entrance to the enclosure means, being
20 operable to induce an exhaust current from the enclosure means.

Preferably, the enclosure means comprises a cabinet housing the washing means and a duct connecting the interior of the cabinet with the interior of the
25 clean room.

Preferably, the washing means comprises a rotary bottle-washing mechanism.

Preferably, the irradiating means comprises ultraviolet lamps.

30 Preferably, the irradiating means produces heat.

Also, in a preferred embodiment, the bottles are supported, during transfer, by a pair of guide rails above the conveyor, which support the necks of the bottles to prevent light plastic bottles from falling.

Embodiments of the present invention will now be described, by way of example, with reference to the accompanying drawings in which:-

Fig. 1 is a diagrammatic plan view of an
5 installation for the washing and transfer to a clean room of bottles, all in accordance with the present invention;

Fig. 2 is a diagrammatic plan view similar to Fig. 1, but showing additional constructional features and
10 modifications; and

Fig. 3 is a sectional elevation on the line III-III in Fig. 2 to a larger scale than Fig. 2.

In Fig. 1 of the drawings, the installation comprises a continuous conveyor 10 for carrying articles
15 in the form of bottles 11 and extending within an enclosure means 12 and into a clean room 13. The enclosure means 12 has an entrance indicated by reference numeral 14 and an exit indicated by reference numeral 15 and disposed within the clean room 13.

20 The enclosure means 12 consists of a cabinet portion 12a which houses a bottle-rinsing mechanism 16 which is disposed adjacent the entrance 14; and the enclosure means 12 further consists of a duct 12b within which is arranged an irradiating means in the form of a
25 bank or banks of ultraviolet lamps 17.

The clean room 13 is bounded by a wall of which a portion is indicated by reference numeral 13a; and it will be understood that the duct 12b passes through the wall portion 13a in such a manner that an air-tight seal
30 is effected between the duct 12b and the wall 13a.

The bottle-rinsing mechanism 16 is operable to rinse and drain the insides of the bottles; and the mechanism is supplied with water incorporating a bactericidal agent, e.g. ozone, by means of a supply

- 5 -

pipe 16a. The rinsing mechanism is drained by means of a drain pipe 16b.

Operation of the above described installation is as follows. The clean room internal air pressure is maintained above ambient pressure in a known manner sufficient to induce an outward air flow through the duct 12b and cabinet 12a. Bottles 11 carried inwards on the continuous conveyor 10 are first subjected to a bactericidal wash by means of the rinsing mechanism 16. On emerging from the rinsing mechanism cabinet 12a, the bottles on the conveyor 10 enter the duct 12b and are subjected to bactericidal radiation from the ultraviolet lamps 17. Thus, the exterior surfaces of the bottles 11 are substantially disinfected as is the inward moving run of the conveyor 10.

The bottles 11 may be supported as they are conveyed along the conveyor 10 by a pair of guide rails (not shown) extending along the conveyor 10 and above it. This rails hold the necks of the bottles 11 to prevent light plastic bottles from falling.

Heat, which is also produced by the lamps 17, assists in vaporising water droplets remaining on the bottles 11 from the previous wash treatment; and an ozone-rich environment is created within the duct 12b and the cabinet 12a which is continuously exhausted at the entrance 14 due to the higher pressure within the clean room 12.

In a modification of the installation described above, a venting means (not shown in Fig. 1) is incorporated in the cabinet 12a adjacent the entrance 14 and operable to induce a positive exhaust current from the enclosure means to ensure a continuous air flow therethrough from the clean room 13. The venting means (not shown in Fig. 1) is preferably an exhaust fan or an exhaust impeller.

The installation described above provides a means for the continuous washing and transfer of bottles into the clean room and accomplishes improved production rates compared with installations hitherto proposed.

5 In Figs. 2 and 3 of the drawings, parts corresponding with those in Fig. 1 are given the reference numerals used in Fig. 1. In Fig. 2, the entrance 14 is provided with a replaceable insert 14a having an aperture configured to match the outline of a
10 bottle 11 as is shown in Fig. 3. This arrangement reduces the opportunity for contaminant dust particles and the like to enter the cabinet 12a at the entrance 14.

 In Fig. 2, the rinsing mechanism 16 is a rotary
15 mechanism known per se. Bottles 11 entering the cabinet 12a on the conveyor 10 are engaged regularly by a feeder worm 18a and carried by a first transfer wheel 19a to an array of radial arms 20 which, whilst turning anti-clockwise, sequentially invert the bottles 11 over spray
20 heads (not shown) for washing and then re-invert the bottles for return to the conveyor 10 by way of a second transfer wheel 19b and feed worm 18b.

 The cabinet 12a is free-standing adjacent the clean room wall 13a except that the cabinet 12a is
25 linked to an aperture in the wall 13a by means of a first duct 12c.

 Within the clean room 13 a second duct 12d encloses the inner end portion of the conveyor 10 and also mutually-opposed banks of ultraviolet lamps 17a.

30 In this embodiment, the conveyor 10 returns at about the inner end of the duct 12d (that is, the exit from the enclosure means defined by the cabinet 12a, duct 12c and duct 12d); and a bottle deflector or "scroll" 22 moves the bottles onto a continuous conveyor
35 21 leading to a bottle-filling station (not shown).

- 7 -

The cabinet 12a is provided with venting means in the form of an exhaust fan 23 which is operable adjustably to ensure a continuous and substantially even air-flow from the clean room 13.

5 Generally, the operation of the Fig. 2/Fig. 3 embodiment is as described with reference to Fig. 1.

CLAIMS

1. A method for effecting continuous washing and transfer of articles to a clean room, comprising the
5 steps of:
conveying the articles continuously on a conveyor means extending within enclosure means and into a clean room, and
within the enclosure means sequentially subjecting
10 the articles to a bactericidal wash and to bactericidal radiation.
2. The method of claim 1, further including the step of inducing an exhaust current from the enclosure means
15 to ensure a continuous air flow there through from the clean room.
3. The method of claim 1 or 2 wherein the articles are bottles intended to be charged with mineral water.
20
4. The method of any preceding claim wherein said bactericidal wash comprises water and ozone.
5. The method of any preceding claim wherein said
25 bactericidal radiation is ultraviolet radiation.
6. Apparatus for the continuous washing and transfer of articles to a clean room, comprising:
a continuous conveyor for conveying the articles
30 and extending within enclosure means and into a clean room, an exit from the enclosure means being within the clean room,
a washing means for use in washing the articles and disposed within the enclosure means adjacent an
35 entrance thereto, and

an irradiating means operable to emit bactericidal radiation towards the conveyor and articles thereon and disposed within the enclosure means downstream of the washing means.

5

7. The apparatus of claim 6 further comprising venting means adjacent the entrance to the enclosure means, being operable to induce an exhaust current from the enclosure means.

10

8. The apparatus of claims 6 or 7 wherein the enclosure means comprises a cabinet housing the washing means and a duct connecting the interior of the cabinet with the interior of the clean room.

15

9. The apparatus of claim 6, 7 or 8 wherein the washing means comprises a rotary bottle-washing mechanism.

20

10. The apparatus of any of claims 6 to 9, wherein the irradiating means comprises ultraviolet lamps.

11. The apparatus of any of claims 6 to 10, wherein the irradiating means produces heat.

1/2








FIG.1.

2/2



2/2



INTERNATIONAL SEARCH REPORT

Intern al Application No

PCT/GB 94/02316

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 6 B08B9/20 B08B5/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B67C B65B B08B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE,A,31 38 215 (H. SILBERZAHN) 3 March 1983 see the whole document see page 9, line 6 - line 9	1-5
A	---	6,7,9,10
X	PATENT ABSTRACTS OF JAPAN vol. 14, no. 327 (M-998) 13 July 1990 & JP,A,02 109 836 (TOPPAN PRINTING CO LTD) 23 April 1990 see abstract	1,5,6,10
Y	---	3,4,9
A	---	2,7
Y	EP,A,0 436 042 (TOYO SEIKAN KAISHA LTD) 10 July 1991 see claims 1-7 see page 4, line 24 - line 31 ---	3,4,9
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

13 February 1995

Date of mailing of the international search report

24.02.95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Lilimpakis, E

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 94/02316

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP,A,0 361 858 (ELOPAK SYSTEMS AG) 4 April 1990 see column 6, line 58 - column 8, line 15	1,5,6,10
Y		4
A		2,7,8
X	--- PATENT ABSTRACTS OF JAPAN vol. 16, no. 419 (C-981) 3 September 1992 & JP,A,04 144 672 (MITSUBISHI HEAVY IND LTD) 19 May 1992 see abstract	1,5
Y		4
A		3,6,10
X	--- CH,A,345 260 (R. JOVIGNOT) 29 April 1960 see page 3, line 99 - page 4, line 74 see page 5, line 113 - page 6, line 17	1-3
A		6-8,11
X	--- PATENT ABSTRACTS OF JAPAN vol. 14, no. 209 (M-968) 27 April 1990 & JP,A,02 045 336 (SNOW BRAND MILK PROD CO) 15 February 1990 see abstract	1,5,6,10
A		2,3
A	--- FR,A,2 129 901 (L' ASEPTISATION S.A.) 3 November 1972 see page 2, line 9 - line 13; claims 1,2 -----	1-3,7,10

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 94/02316

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE-A-3138215	03-03-83	DE-A- 3033043	11-03-82
		AT-B- 382315	10-02-87
		BE-A- 890190	04-01-82
		FR-A,B 2489153	05-03-82
		GB-A,B 2084550	15-04-82
		NL-A- 8104065	01-04-82
		US-A- 4409188	11-10-83

EP-A-0436042	10-07-91	JP-A- 3056222	11-03-91
		WO-A- 9101918	21-02-91

EP-A-0361858	04-04-90	NONE	

CH-A-345260		NONE	

FR-A-2129901	03-11-72	NONE	
